
YIOSI

INSTALLATION GUIDE

Ceramic Heart Leaf Linear Dining Pendant L1200

LINEAR PENDANT · CEILING MOUNT



Model **YIOSI-0527** · **YIOSI-0528**

Please read this guide completely before you begin, and keep it for future reference.

BEFORE YOU BEGIN

⚠ **WARNING**

- **Turn off the power at the circuit breaker** before installing, changing bulbs or cleaning the fixture.
- Installation by a **qualified electrician** is recommended. Install in accordance with local electrical codes.
- This fixture uses 6 G9 bulbs. Do not exceed the wattage rating marked on the lamp holders.
- Do not clean the fixture with corrosive substances such as gasoline or alcohol-based disinfectants.
- Use this fixture only for its intended purpose. Do not modify or rewire it.
- Keep small parts and packaging away from children. They can cause serious injury.


PREPARATION

- Read every step carefully and follow them in order.
- Unpack and check all parts against the parts list. If anything is missing or damaged, contact us before installing (see the last page). We will send replacement parts promptly.
- Assemble the fixture where it will be installed. Moving it mid-assembly risks losing small parts.

SPECIFICATIONS

LIGHT SOURCE	LENGTH	MOUNTING
6 × G9 bulbs	**1200 mm**	**Ceiling, adjustable cables**

IN THE BOX




PART	QTY	DESCRIPTION
A	× 1	Canopy with mounting plate
B	× 1	Centre body with arms
C	× 1	Branch
D	× 36	Large ceramic leaf
E	× 36	Small ceramic leaf
F	× 6	Glass shade
—	× 1	Hardware kit (screws, wire connectors, hex key, leaf fittings)

INSTALLATION

STEP 1

Assemble the frame


Thread the power cord of the centre body up through the canopy (A) and tighten the side screws. Fit the branches (C) to the body as shown, threading the wires through in order, and fasten them.



STEP 2

Mount the plate


Turn off the power at the circuit breaker. Remove the mounting plate from the canopy (A) and fix it to the ceiling junction box with the screws.



STEP 3

Connect the wires


Join the fixture wires to the matching house supply wires with the wire connectors: live to live, neutral to neutral, ground to ground. Then lift the canopy (A) to the plate and fasten it.



STEP 4

Set the height


Hold the cable gripper under the canopy and slide the cables to adjust the hanging height to suit your room.



STEP 5

Fit the leaves, bulbs and shades

Fix the large (D) and small (E) ceramic leaves to the branches in a staggered pattern and adjust their angle. Insert the 6 G9 bulbs, screw on the glass shades (F) and make sure every wire safety clip is fastened. Restore power and switch on to test.



CARE & SUPPORT

CLEANING & CARE

- Clean the fixture about once a month to keep it looking its best.
- Turn off the power and let the fixture cool to room temperature first.
- Wipe with a soft cloth dampened with water and wrung dry. Never spray liquid directly onto the fixture.
- Do not use gasoline, alcohol or other corrosive cleaners.

GOOD TO KNOW

- Use the fixture only as designed. Damage caused by modification, third-party parts or natural disasters is not covered.
- Warranty terms are listed at yiosilamp.com.

NEED HELP?

support@yiosilamp.com

+1 970-896-9411

Missing parts, installation questions or anything else, we are here to help. Please include your order number and a photo of the issue so we can resolve it quickly.