
YIOSI

INSTALLATION GUIDE

31.5" 6-Tier Alabaster Chandelier

CHANDELIER · CEILING MOUNT



Model **YIOSI-0563**

Please read this guide completely before you begin, and keep it for future reference.

BEFORE YOU BEGIN

⚠ **WARNING**

- **Turn off the power at the circuit breaker** before installing, changing bulbs or cleaning the fixture.
- Installation by a **qualified electrician** is recommended. Install in accordance with local electrical codes.
- This fixture requires 16 E12 bulbs, max. 40 W each. Do not exceed the rated wattage.
- Do not clean the fixture with corrosive substances such as gasoline or alcohol-based disinfectants.
- Use this fixture only for its intended purpose. Do not modify or rewire it.
- Keep small parts and packaging away from children. They can cause serious injury.
- Fix the chandelier to a support strong enough to carry its full weight, such as a ceiling joist.


PREPARATION

- Read every step carefully and follow them in order.
- Unpack and check all parts against the parts list. If anything is missing or damaged, contact us before installing (see the last page). We will send replacement parts promptly.
- Assemble the fixture where it will be installed. Moving it mid-assembly risks losing small parts.
- This guide shows one size. Other sizes in the same series install the same way.

SPECIFICATIONS

LIGHT SOURCE	MAX. WATTAGE	MOUNTING
16 × E12 bulbs	**40 W per bulb**	**Ceiling, adjustable chain**

IN THE BOX




PART	QTY	DESCRIPTION
A	× 4	Screw with wall anchor
B	× 3	Wire connector
C	× 1	Mounting bracket
D / E	× 1 / 1	Canopy / chain
F	× 1	Top ring
H	× 1	Middle ring
J	× 1	Bottom ring
G / I	× 3 / 1	Connecting rod / center rod
K	× 1	Lamp body
L	× 89	Alabaster leaf

INSTALLATION

STEP 1

Assemble the frame


Hang the lamp body (K) inside the top ring (F). Join the middle ring (H) below it with the connecting rods (G), and hang the bottom ring (J) from the center rod (I), as shown.



STEP 2

Mount the bracket


Turn off the power at the circuit breaker. Fix the mounting bracket (C) to the ceiling with the screws and anchors (A). Join the fixture wires to the matching house supply wires with the wire connectors (B): live to live, neutral to neutral, ground to ground.



STEP 3

Hang the chandelier


Fix the canopy (D) to the bracket. Hang the frame from the chain (E) and adjust the chain to the height you want.



STEP 4

Fit the bulbs and alabaster

Install the 16 E12 bulbs. Hang the alabaster leaves (L) on the hooks of each ring, tier by tier, as shown. Restore power and switch on to test.



CARE & SUPPORT

CLEANING & CARE

- Clean the fixture about once a month to keep it looking its best.
- Turn off the power and let the fixture cool to room temperature first.
- Wipe with a soft cloth dampened with water and wrung dry. Never spray liquid directly onto the fixture.
- Do not use gasoline, alcohol or other corrosive cleaners.

GOOD TO KNOW

- Use the fixture only as designed. Damage caused by modification, third-party parts or natural disasters is not covered.
- Warranty terms are listed at yiosilamp.com.
- Natural alabaster varies piece to piece. Veining and tone differences are part of its character.

NEED HELP?

support@yiosilamp.com

+1 970-896-9411

Missing parts, installation questions or anything else, we are here to help. Please include your order number and a photo of the issue so we can resolve it quickly.