
YIOSI

INSTALLATION GUIDE

Pineapple Bead Crystal Flush Mount 560

FLUSH MOUNT · CEILING



Model **YIOSI-0609**

Please read this guide completely before you begin, and keep it for future reference.

BEFORE YOU BEGIN

⚠ **WARNING**

- **Turn off the power at the circuit breaker** before installing, changing bulbs or cleaning the fixture.
- Installation by a **qualified electrician** is recommended. Install in accordance with local electrical codes.
- This fixture requires 9 E12 bulbs, max. 40 W each. Do not exceed the rated wattage.
- Do not clean the fixture with corrosive substances such as gasoline or alcohol-based disinfectants.
- Use this fixture only for its intended purpose. Do not modify or rewire it.
- Keep small parts and packaging away from children. They can cause serious injury.


PREPARATION

- Read every step carefully and follow them in order.
- Unpack and check all parts against the parts list. If anything is missing or damaged, contact us before installing (see the last page). We will send replacement parts promptly.
- Assemble the fixture where it will be installed. Moving it mid-assembly risks losing small parts.
- This guide shows one size. Other sizes in the same series install the same way.

SPECIFICATIONS

LIGHT SOURCE	MAX. WATTAGE	MOUNTING
9 × E12 bulbs	**40 W per bulb**	**Ceiling, flush**

IN THE BOX




PART	QTY	DESCRIPTION
A	× 4	Screw with nut
B	× 3	Wire connector
C	× 1	Mounting bracket
D	× 1	Nut
E	× 1	Lamp body
F	× 50	Crystal prism
G	× 21	Crystal bead strand
H	× 13	Crystal bead strand
I	× 7	Crystal bead strand
J	× 1	Crystal bead strand, center

INSTALLATION

STEP 1

Mount the bracket


Turn off the power at the circuit breaker. Fix the mounting bracket (C) to the ceiling junction box with the screws (A).



STEP 2

Connect and fix the lamp body


Join the fixture wires to the matching house supply wires with the wire connectors (B): live to live, neutral to neutral, ground to ground. Lift the lamp body (E) up to the bracket and fasten it with the nuts.



STEP 3

Fit the bulbs


Install the 9 E12 bulbs in the lamp holders.



STEP 4

Hang the crystals

Hang the crystal prisms (F) around the rim, then hang the crystal bead strands (G, H, I) and the center strand (J) inside, as shown. Restore power and switch on to test.



CARE & SUPPORT

CLEANING & CARE

- Clean the fixture about once a month to keep it looking its best.
- Turn off the power and let the fixture cool to room temperature first.
- Wipe with a soft cloth dampened with water and wrung dry. Never spray liquid directly onto the fixture.
- Do not use gasoline, alcohol or other corrosive cleaners.

GOOD TO KNOW

- Use the fixture only as designed. Damage caused by modification, third-party parts or natural disasters is not covered.
- Warranty terms are listed at yiosilamp.com.

NEED HELP?

support@yiosilamp.com

+1 970-896-9411

Missing parts, installation questions or anything else, we are here to help. Please include your order number and a photo of the issue so we can resolve it quickly.