
YIOSI

INSTALLATION GUIDE

Inverted Triangle Crystal Round Pendant 1000

CHANDELIER · CEILING MOUNT



Model **YIOSI-0640**

Please read this guide completely before you begin, and keep it for future reference.

BEFORE YOU BEGIN

⚠ **WARNING**

- **Turn off the power at the circuit breaker** before installing, changing bulbs or cleaning the fixture.
- Installation by a **qualified electrician** is recommended. Install in accordance with local electrical codes.
- This fixture uses 12 E12 bulbs, 3 W each (supplied). Replace only with bulbs of the same type and rating.
- Do not clean the fixture with corrosive substances such as gasoline or alcohol-based disinfectants.
- Use this fixture only for its intended purpose. Do not modify or rewire it.
- Keep small parts and packaging away from children. They can cause serious injury.
- For indoor use only.


PREPARATION


- Read every step carefully and follow them in order.
- Unpack and check all parts against the parts list. If anything is missing or damaged, contact us before installing (see the last page). We will send replacement parts promptly.
- Assemble the fixture where it will be installed. Moving it mid-assembly risks losing small parts.

SPECIFICATIONS

LIGHT SOURCE	COLOR TEMPERATURE	MOUNTING
12 × E12 bulbs, 3 W each (included)	**2700K**	**Ceiling, adjustable cables**

IN THE BOX






PART	QTY	DESCRIPTION
A	× 1	Canopy (ceiling plate)
B	× 8	Support, 115 mm
C	× 1	Ring, D780
D	× 12	E12 bulb
E	× 8	Support, 265 mm
F	× 1	Ring, D520
G	× 4	Support, 415 mm
H	× 1	Ring, D260
I	× 450	Crystal strip
—	× 1	Hardware pack (gloves, wire connectors, screws, wall anchors, small fittings)

INSTALLATION

STEP 1

Mount the crossbar


Turn off the power at the circuit breaker. Remove the crossbar from the canopy (A) and fix it to the ceiling junction box with the screws.



STEP 2

Build the lower tiers


Take out the lamp body and check that it is firm. Fit the supports (B, E, G) into the bracket under the lamp body and lock the rings onto them tier by tier: the D780 ring (C), then the D520 ring (F), then the D260 ring (H), as shown.



STEP 3

Hang and connect


Join the fixture wires to the matching house supply wires with the wire connectors: live to live, neutral to neutral, ground to ground. Fix the canopy (A) to the crossbar, then set the hanging cables to the height you want.



STEP 4

Fit the bulbs and crystals

Screw the E12 bulbs (D) into the lamp holders. Hang the crystal strips (I) on the flat rings all the way round. Restore power and switch on to test.



CARE & SUPPORT

CLEANING & CARE

- Clean the fixture about once a month to keep it looking its best.
- Turn off the power and let the fixture cool to room temperature first.
- Wipe with a soft cloth dampened with water and wrung dry. Never spray liquid directly onto the fixture.
- Do not use gasoline, alcohol or other corrosive cleaners.

GOOD TO KNOW

- Use the fixture only as designed. Damage caused by modification, third-party parts or natural disasters is not covered.
- Warranty terms are listed at yiosilamp.com.
- The canopy suits flat and sloped ceilings.
- Each fixture is handmade, so slight variations in dimensions may occur.

NEED HELP?

support@yiosilamp.com

+1 970-896-9411

Missing parts, installation questions or anything else, we are here to help. Please include your order number and a photo of the issue so we can resolve it quickly.