
YIOSI

INSTALLATION GUIDE

Modern 4-Tier Alabaster Round Chandelier

CHANDELIER · CEILING MOUNT



Model **YIOSI-0724**

Please read this guide completely before you begin, and keep it for future reference.

BEFORE YOU BEGIN

⚠ **WARNING**

- **Turn off the power at the circuit breaker** before installing, changing bulbs or cleaning the fixture.
- Installation by a **qualified electrician** is recommended. Install in accordance with local electrical codes.
- This fixture requires 6 E12 bulbs, max. 40 W each. Do not exceed the rated wattage.
- Do not clean the fixture with corrosive substances such as gasoline or alcohol-based disinfectants.
- Use this fixture only for its intended purpose. Do not modify or rewire it.
- Keep small parts and packaging away from children. They can cause serious injury.


PREPARATION

- Read every step carefully and follow them in order.
- Unpack and check all parts against the parts list. If anything is missing or damaged, contact us before installing (see the last page). We will send replacement parts promptly.
- Assemble the fixture where it will be installed. Moving it mid-assembly risks losing small parts.
- This guide shows one size. Other sizes in the same series install the same way.

SPECIFICATIONS

LIGHT SOURCE	MAX. WATTAGE	MOUNTING
6 × E12 bulbs	**40 W per bulb**	**Ceiling, adjustable chain**

IN THE BOX



PART	QTY	DESCRIPTION
A	× 4	Screw
B	× 3	Wire connector
C	× 1	Mounting bracket
D, E	× 1 + 2	Canopy and canopy cap nuts
F	× 1	Chain
G, I	× 1 + 1	Center rod and hook rod
H, J	× 1 + 1	Upper and lower hook frames
K	× 1	Lamp holder cluster
L	× 45	Alabaster piece

INSTALLATION

STEP 1

Assemble the frame


Fit the upper and lower hook frames (H, J) and the lamp holder cluster (K) onto the center rod (G) as shown, and hang the frame from the chain (F). Adjust the chain to the length you need.



STEP 2

Mount the bracket


Turn off the power at the circuit breaker. Remove the mounting bracket (C) from the canopy and fix it to the ceiling junction box with the screws (A).



STEP 3

Connect the wires


Join the fixture wires to the matching house supply wires with the wire connectors (B): live to live, neutral to neutral, ground to ground. Tuck the connections neatly into the junction box.



STEP 4

Hang the frame

Lift the canopy (D) up to the bracket and fasten it with the canopy cap nuts (E). Screw the six E12 bulbs into the lamp holders.






STEP 5

Hang the alabaster pieces

Wearing clean gloves, hang the alabaster pieces (L) on the hooks of each tier, working from the top tier down. Restore power and switch on to test.



CARE & SUPPORT

CLEANING & CARE

- Clean the fixture about once a month to keep it looking its best.
- Turn off the power and let the fixture cool to room temperature first.
- Wipe with a soft cloth dampened with water and wrung dry. Never spray liquid directly onto the fixture.
- Do not use gasoline, alcohol or other corrosive cleaners.

GOOD TO KNOW

- Use the fixture only as designed. Damage caused by modification, third-party parts or natural disasters is not covered.
- Warranty terms are listed at yiosilamp.com.
- Natural alabaster varies piece to piece. Veining and tone differences are part of its character.

NEED HELP?

support@yiosilamp.com

+1 970-896-9411

Missing parts, installation questions or anything else, we are here to help. Please include your order number and a photo of the issue so we can resolve it quickly.